Application No. (if known): 09/759,806

Attorney Docket No.: 01641/100K021-US1

Certificate of Express Mailing Under 37 CFR 1.10

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail, Airbill No. 994070399-05

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

on February 11, 2004

Date

Signature
Signature
Typed or printed name of person signing Certificate

Note: Each paper must have its own certificate of mailing, or this certificate must identify

each submitted paper.

Information Disclosure Statement (2 pages) IDS (Citation) by Applicant (1 page)

2 References Cited

Check in the amount of \$180.00

Certificate of Express Mail

Return Postcard

FEB 11 2004 2 1/19/1 1/19/1 (c) 2004 Thomson Derwent WPI (c) 2004 Thomson Derwent. All rts. reserv.

011637084 **Image available**
WPI Acc No: 1998-053992/ 199806

XRPX Acc No: N98-042707

Catadioptric system for object image projection ion photolithography - comprises first and second imaging systems with optical axes and concave mirror, with associated light flux separator

Patent Assignee: NIKON CORP (NIKR)

Inventor: OMURA Y

Number of Countries: 003 Number of Patents: 003

Patent Family:

Patent No Applicat No Kind Date Kind Date Week DE 19726058 A1 19980102 DE 1026058 19970619 199806 B Α JP 10010431 Α 19980116 JP 96180013 19960620 199813 Α KR 98005328 19980330 KR 9721294 Α 19970528 199904

Priority Applications (No Type Date): JP 96180013 A 19960620

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

DE 19726058 A1 20 G03F-007/20 JP 10010431 A 12 G02B-017/08 KR 98005328 A H01L-021/027

Abstract (Basic): DE 19726058 A

The system has a first imaging system (S1), with an optical axis, and which effects a magnification. The light from the object (m) is received by the imaging system and deflected by its concave mirror (CM) to generate an intermediate image.


A second imaging system (S2), with an optical axis, receives the light from the intermediate image and generates a reduced size image of the object on the substrate (w). A light flux separator (M1), near the intermediate image, either passes light from the object to the concave mirror, or passes the mirror reflected light to the second imaging system.

USE - For manufacture of integrated circuits.

ADVANTAGE - High work spacing, high resolution images, and suitable for use with shortwave light.

Dwg.1/4

C:\Program Files\Dialog\DialogLink\Graphics\378.bmp



Title Terms: CATADIOPTRIC; SYSTEM; OBJECT; IMAGE; PROJECT; ION; PHOTOLITHOGRAPHIC; COMPRISE; FIRST; SECOND; IMAGE; SYSTEM; OPTICAL; AXIS; CONCAVE; MIRROR; ASSOCIATE; LIGHT; FLUX; SEPARATE

Derwent Class: P81; P84; U11

International Patent Class (Main): G02B-017/08; G03F-007/20; H01L-021/027

International Patent Class (Additional): G02B-013/14; G02B-013/18;

G02B-013/24

File Segment: EPI; EngPI

Manual Codes (EPI/S-X): U11-C04C2; U11-C04E2